

# SRS ViVA 1 topsynth ultra



## Longlife High Performance Engine Oil

January 2024

### Characteristics

**SRS ViVA 1 topsynth ultra** is a high performance low friction SAE 5W-30 engine oil for year-round use in modern gasoline and diesel engines. Selected Base oils of the latest synthesis technology and the modern additives with lowered sulphate ash ensure high wear protection. Excellent cold-start behaviour ensures optimum lubrication reliability in the cold-running phase.

SRS ViVA 1 topsynth ultra helps to protect the environment by reducing emissions and fuel consumption. Extreme loads and high temperatures are safely handled under all operating conditions.

### Applications

**SRS ViVA 1 topsynth ultra** is especially recommended for gasoline and diesel engines with emission reduction systems to fulfil the emission standards Euro VI. This engine oil maintains the effectiveness of emission reduction systems over extended running times.

### Specifications

- SAE-Klasse 5W-30
- ACEA C2 / C3
- API SP

### Approvals

- MB-Approval 229.52
- MB-Approval 229.51
- MB-Approval 229.31
- BMW Longlife-04

### Recommendations

- Opel / Vauxhall OV 0401547-G30
- Opel / Vauxhall OV 0401547-D30
- VW 505 01 and 505 00

SRS ViVA 1 topsynth ultra is a product of the H&R ChemPharm GmbH.

Typical Data	Test Method	SRS ViVA 1 topsynth ultra
SAE Grade	SAE J 300	5W-30
Density at 15°C	DIN 51 757	0.850
Dyn. Viscosity at -30°C (CCS)	ASTM D 5293	5,660
Kin. Viscosity at 40°C	DIN EN ISO 3104	70
Kin. Viscosity at 100°C	DIN EN ISO 3104	11.9
Viscosity Index (VI)	DIN ISO 2909	167
Flash Point COC	DIN EN ISO 2592	238
Pour Point	DIN EN ISO 3016	- 39

The above values may vary within the commercial limits.

**Made in Germany**

