

SRS Rekord plus



High Performance Monograde Engine Oils

August 2024

Characteristics

SRS Rekord plus are special high performance monograde engine oils. The performance covers the requirements of MTU oil category 2, MAN M 3275-2 and MB-Sheet 228.2 for monograde engine oils.

Application

SRS Rekord plus is recommended for use in heavy duty marine engines with extended oil drain intervals. It is also suitable for use in diesel engines of agricultural and construction vehicles as well as of stationary industrial installations.

Specifications

- SAE Grade 30 and 40
- ACEA E7
- API CI-4 / SL

Approvals

- MTU MTL 5044 Type 2

Recommendations

- MB 228.2H
- MAN M 3275-2
- Allison C-4

SRS Rekord plus engine oils are products of the H&R ChemPharm GmbH.

Typical Data	Test Method	SRS Rekord plus	
		30	40
SAE Grade	SAE J 300	30	40
Density at 15°C	DIN 51 757	0.892	0.893
Kin. Viscosity at 40°C	DIN EN ISO 3104	101	129
Kin. Viscosity at 100°C	DIN EN ISO 3104	11.8	13.9
Viscosity Index (VI)	DIN ISO 2909	107	105
Flash Point COC	DIN ISO 2592	250	270
Pour Point	DIN ISO 3016	-30	-27
Total Base Number	DIN ISO 3771	10.8	10.8

The above values may vary within the commercial limits.

Made in Germany

